

<b>Product Name</b>	<b>Burglary Fire Safe</b>
<b>Model No.</b>	<b>HS 2214</b>
<b>Specifications</b>	
<ol style="list-style-type: none"> <li>1. 3-3/4" Thick door consisting of 1/4", and two 1/8" thick steel plates with 2" of fire insulation</li> <li>2. 2" Thick body consisting of 1/8" thick, inner and outer steel plates with with 1-3/4" of fire insulation</li> <li>3. One recessed bolt down hole with cover and Bolt down hardware included</li> <li>4. Heavy duty solid steel block ball bearing hinges</li> <li>5. Class 350 degree, 105 minutes fire MFG label</li> <li>6. In tumescent door seal when exposed to high temperature expands to as much as 8 times its thickness</li> <li>7. 3 mm V shape harden Anti-drill steel plate to protect side punch attack to the bolt works</li> <li>8. Supplied with UL Group II combination or electronic lock</li> <li>9. Comes standard with your choice of Securam Electronic lock or Dial Combination Lock</li> </ol>	

<b>External Dimensions</b>	<b>Internal Dimensions</b>	<b>Weight</b>	<b>Shelf</b>
H X W X D (Inch)		(Lbs.)	
22 x 14 x 16	17 x 10 x 10.7	160	2



*Protecting Canadians Coast to Coast*